

# SAMPLING PUMP



## Features

This type of sampling pump is specially designed for GS40 Multi-Gas Detector, which can be easily assembled and disassembled with GS40 Multi-Gas Detector. After being equipped with sampling pump, GS40 Multi-Gas Detector can protect personnel better who needs to work under confined circumstances with undefined dangerous gas.



## Specifications

<b>Part No.</b>	<b>90008000</b>
	<b>Used with GS40 Multi-Gas Detector</b>
<b>Sampling Probe</b>	<b>Available</b>
<b>Flowing Rate</b>	<b>600ml/min</b>
<b>Power</b>	<b>High capacity Li-polymer battery</b>
	<b>Voltage, 3.7V</b>
	<b>Capacity, 1500 mAh</b>
<b>Run Time</b>	<b>12 hours</b>
<b>Alarm method</b>	<b>Sound, light alarms</b>
<b>Protection Classification</b>	<b>IP64</b>
<b>Environment Temperature</b>	<b>-20°C ~ 50°C</b>
<b>Environment Humidity</b>	<b>15%~ 95% relative humidity (standard)</b>
<b>Explosion-Proof</b>	<b>Ex ia IIC T6 or Ex ib I</b>
<b>Size</b>	<b>155mm*70mm*402mm (length*width*height)</b>
<b>Weight</b>	<b>200 g</b>
<b>Materials of the cases</b>	<b>Antistatic ABS</b>

For more information, please contact Ennix Technology at [info@ennix-gas.com](mailto:info@ennix-gas.com).